

# E18MML

## DRIVEABLE VERTICAL LIFT

VERTICAL LIFT



### KEY FEATURES

- Designed with the operator in mind, featuring familiar controls, Point & Go steer, ergonomic joystick and ease of entry/exit from platform.
- Increase productivity with longer running AGM batteries.
- Lightweight and compact footprint is ideal for sensitive flooring and accessing tight spaces with high transportability.
- Quick access to key, known scissor components and durable mast protection offers efficient serviceability to maximize uptime with new LCD display showing fault codes and maintenance information.



### Performance - INDOOR ONLY

Platform Height (Elevated)	5.5 m
Working Height	7.5 m
Platform Capacity	181 kg
Work Tray Capacity	45 kg
Number of Occupants	1
Lift / Lower Time†	23/23 seconds
Maximum Drive Height	Fully Elevated
Weight*	870 kg
Drive Speed (Elevated)	0.8 km/h
Drive Speed (Lowered)	4 km/h
Gradeability	30%
Turning Radius (Inside)	Zero
Turning Radius (Outside)	1.2 m

### Machine Dimensions

Platform Height (Lowered)	1.98 m
Platform Entry Height	0.47 m
Platform With Tray Lowered (W x L)	0.71 m x 0.75 m
Platform With Tray Lifted (W x L)	0.71 m x 1.43 m
Machine Width x Length	0.76 m x 1.35 m
Machine Length with Tray Lifted	2.06 m
Wheelbase	1.05 m
Ground Clearance	6.35 cm

### Power Source

Battery	Four Sealed-AGM 6V - 220 AH (180 duty cycles)
Charger	27 amp
Drive	4 Brush Direct Electric Drive (Planetary Gear)

### Lift & Steer Systems

Lift	Hydraulic
Steer	Point & Go

### Tyres

Front	0.20 m Castors Non-Marking
Rear	0.25 m x 0.07 m Non-Marking

### Brakes

Electric

### Standard Features

- Platform with Work Tray and Drop Bar
- Active Pothole Protection System
- All Motion Alarm
- Multi-Function Universal Charger
- Analyzer Port for Diagnostics
- Battery Condition Indicator
- DC Electric Drive
- Dynamic Braking
- Electric Brake Release
- Fork Lift Pockets
- Greaseless Kingpin Joints
- Horn
- Hourmeter
- Lanyard Attach Points
- LCD Display for Fault Code Information
- Lifting and Tie Down Points
- Load Sensing System
- Maintenance Indicator
- Manual Descent
- Mast Maintenance Prop
- Onboard Diagnostic System
- Proportional Controls
- Amber Beacon
- USB/ Phone Cradle
- Tilt Alarm and Light
- Telematics Ready

### Accessories & Options

- Ceiling Tile Platform (0.56 m x 0.66 m)
- Platform with Extension Deck ( 0.75 m x 1.30 m )
- Anti-Vandalism Package
- CleanGuard™
- ClearSky™
- Crane Hook
- JLG Mobile Control
- Front and Side Bumpers
- Gate Alarm

### The JLG "1 & 5" Warranty

JLG Industries, Inc., backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.

### JLG Industries (Australia)

358 Park Road  
Regents Park, NSW 2143  
Telephone 02 8718 6300  
Fax 02 8718 6377

[www.jlg.com.au](http://www.jlg.com.au)

An Oshkosh Corporation Company